

# Secura PUR

## PRODUCT SPECIFICATION

### Key Features

- > Wood, parquet & stone designs
- > Loose lay luxury vinyl sheet
- > Available in 2m, 3m & 4m roll widths
- > 19dB acoustic performance
- > Light commercial & residential



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm
Wear Layer	ISO 24340 (EN 429)	0.35mm
Total Weight	ISO 23997 (EN 430)	1780g/m <sup>2</sup>
Finish		PUR

Sheet Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	4m x 20-25m	18	-	80-100m <sup>2</sup>
	3m x 20-25m	18	-	60-75m <sup>2</sup>
	2m x 20-25m	18	-	40-50m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 26986 (EN 653)	Conforms
Use Area	ISO 10874 (EN 685)	23, 32, 41
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B	Class DS R10
Abrasion Resistance	EN 653	Group T
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1	≤0.20mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Furniture Leg	ISO 16581 (EN 424)	Pass
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435)	(Method A) Pass 20mm ø
Thermal Resistance	EN 12667	0.0525m <sup>2</sup> K/W 0.525 Tog
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

## Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
Generic EN 15804 EPD		Available
Recyclable & Reusable		100%
Recyclable Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

## Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	19dB

## Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



### Polyflor Ltd. Head Office


PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

## RANGE SHADES



**Oakland Parquet 2167**  
plank size in sheet: 88 x 700mm  
LRV 38



**Grey Oak Parquet 2168**  
plank size in sheet: 88 x 700mm  
LRV 37



**White Limed Ash 2160**  
plank size in sheet: 166 x 1500mm  
LRV 57



**Coastal Oak 2159**  
plank size in sheet: 200 x 1500mm  
LRV 37



**Sterling Oak 2161**  
plank size in sheet: 200 x 1000mm  
LRV 40



**Blond Oak 2127**  
plank size in sheet: 200 x 1500mm  
LRV 42



**Golden Oak 2128**  
plank size in sheet: 62.5 x 500-1000mm  
LRV 37



**Wheatfield Oak 2163**  
plank size in sheet: 167 x 1500mm  
LRV 39




**Natural Oak 2126**  
plank size in sheet: 200 x 1000mm  
LRV 32



**Honey Blushed Oak 2162**  
plank size in sheet: 200 x 1500mm  
LRV 30




**Country Oak 2130**  
plank size in sheet: 200 x 1500mm  
LRV 20



**Antique Herringbone 2129**  
plank size in sheet: 140 x 710mm  
LRV 20



**Ebony 2135**  
plank size in sheet: 100-150 x 1000mm  
LRV 12



**Limestone 2111**  
plank size in sheet: 333 x 500mm  
LRV 55



**Powdered Concrete 2164**  
NCS S 3000-N  
LRV 40



**Polished Concrete 2118**  
NCS S 5502-Y  
LRV 23



**Plymouth Slate 2165**  
plank size in sheet: 333 x 500mm  
LRV 18



**Black Slate 2114**  
plank size in sheet: 333 x 500mm  
LRV 8

LRV - Light Reflectance Value

NCS - Natural Colour System

**Polyflor Ltd. Head Office**

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1