

POLYFLOR BEVEL LINE WOOD PU

- Captures the natural beauty of wood
- Authentic reproductions of real materials
- Design accessories available upon request

SPECIFICATION



BEVELline™
THE WOOD & STONE COLLECTION

WOOD

LUXURY VINYL
TILES



GENERAL PERFORMANCE
EN 649



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass
ASTM E648 Class 1



SLIP RESISTANCE
EN 13893 Class DS (dry condition)*
AS/NZS 4586 R9



LIGHT FASTNESS
ISO 105-B02 Method 3 ≥6



ABRASION RESISTANCE
EN 649 Group T



INDENTATION - RESIDUAL
EN 433 ≤ 0.1mm



DIMENSIONAL STABILITY
EN 434 ≤ 0.25% max.



CASTOR CHAIR (continuous use)
Suitable



THERMAL CONDUCTIVITY
Suitable for underfloor heating Max. 27°C



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Bevel Line PU achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as education, healthcare and retail. Bevel Line PU is 100% recyclable and contains 15% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



APPLICATIONS
Bevel Line is ideal for all residential areas and heavy commercial areas such as hotels, offices, schools, hospitals, airports and department stores.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
At the date of issue the data presented is correct.
* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR

PERFORMANCE AND
PROPERTIES

A+BRE
ENP 429
ENVIRONMENTAL
RATING
Refer to BRE Global ratings
on www.greenbooklive.com



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



POLYFLOR™
COVERING THE WORLD