

**POLYFLOR CAMARO STONE & DESIGN PU**

- Camaro - collection of versatile vinyl floor products
- Stone, slate and marble effect floorcovering designs
- Coordinating grouting, marquetry and feature strips are readily available to blend, shape or accentuate design ideas

**SPECIFICATION**



2.0mm



0.3mm



36 @ 305 x 305mm = 3.34m<sup>2</sup>  
 \*18 @ 610 x 305mm = 3.34m<sup>2</sup>  
 ▲16 @ 457 x 457mm = 3.34m<sup>2</sup>



3600g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
**EN 649**  
**F1303-99** Type I Grade 2



**REACTION TO FIRE**  
**EN ISO 13501-1** Class Bfl-S1 { **EN ISO 9239-1** ≥8kw/m<sup>2</sup>  
**EN ISO 11925-2** Pass



**SLIP RESISTANCE**  
**EN 13893** Class DS (dry condition)\*  
**AS/NZS 4586** R9



**LIGHT FASTNESS**  
**ISO 105-B02** Method 3 ≥6



**ABRASION RESISTANCE**  
**EN 649** Group T



**ELECTRICAL BEHAVIOUR (body voltage)**  
**EN1815** This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



**INDENTATION - RESIDUAL**  
**EN 433** ≤ 0.1mm



**DIMENSIONAL STABILITY**  
**EN 434** ≤ 0.25%



**CASTOR CHAIR (continuous use)**  
 Suitable



**THERMAL CONDUCTIVITY**  
 Suitable for underfloor heating Max. 27°C



**ENVIRONMENTALLY PREFERABLE FLOORING**  
 Polyflor Camaro PU achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as retail. Camaro PU is 100% recyclable and contains 15% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at [www.polyflor.com/environment](http://www.polyflor.com/environment)



**APPLICATIONS**  
 Polyflor Camaro PU is suitable for use in any domestic situation and moderate commercial areas such as offices, hotels and boutiques.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).  
 \* For clarification regarding slip resistance, consult Polyflor.

**VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.**

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
 WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)



**CAMARO**<sup>TM</sup>  
 FLOORING COLLECTION

**STONE & DESIGN**

**PERFORMANCE AND PROPERTIES**



Refer to BRE Global ratings on [www.greenbooklive.com](http://www.greenbooklive.com)

