



- The following maintenance instructions are designed to minimise the cost factor, while ensuring that your floorcovering retains the optimum appearance and performance.
- Polysafe Wood FX Acoustic is reinforced with polyurethane for improved cleaning and maintenance - this ensures that - even after transportation, installation and the period prior to handover - the intensity of construction clean can be significantly reduced. This will have a beneficial impact on the initial costs.

**INITIAL CONSTRUCTION CLEAN**

- Remove all loose debris.
- Remove surface dust and grit by sweeping or vacuuming.
- Apply a solution of neutral cleanser (or alkaline cleanser, dependent upon the level of soiling), diluted to the manufacturer's instructions, with a spray over the section to be cleaned. Leave for sufficient time to react with the soiling.
- Pick up the solution with a clean microfibre mop, using a continuous side-to-side motion. When the mop head becomes loaded, it will start streaking the floor. At this point the dirty mop head should be removed and placed into a laundry bag and a clean mop head fitted. The cycle should then be repeated until the whole floor is completed.
- The dirty mop heads should then be laundered, in preparation for reuse.

**ROUTINE MAINTENANCE**

The method of maintenance chosen from the options below is dependent on the level of traffic in the use area. Contact Polyflor Customer Technical Services for more details.

**MICRO FIBRE MOP**

- Remove surface dust and grit by sweeping or vacuum.
- Apply a solution of neutral cleanser (or alkaline cleanser, dependent upon the level of grease or oily contaminates), diluted to the manufacturer's instructions, with a spray over the section to be cleaned. Leave for sufficient time to react with the soiling.
- Pick up the solution with a clean microfibre mop, using a continuous side-to-side motion. When the mop head becomes loaded, it will start streaking the floor. At this point the dirty mop head should be removed and placed into a laundry bag and a clean mop head fitted. The cycle should then be repeated until the whole floor is completed.
- The dirty mop heads should then be laundered, in preparation for reuse.
- The maximum benefits are derived from this system by carrying out this quick and simple procedure on a daily basis, and by using clean equipment each time, to maximise dirt pick-up and eliminate streaking.

**ROTARY MACHINE SCRUBBER**

- Sweep, mop sweep or dry vacuum the floor to remove dust and loose dirt.
- Spot mop regularly. Stubborn black marks can be removed by using the centre disc of a scrubbing pad and a small amount of undiluted alkaline cleanser. Place the disc under the sole of a shoe and rub - this gives greater pressure. Rinse the area well with clean warm water and leave to dry.
- Apply a solution of neutral or alkaline cleanser, diluted to the manufacturer's instructions, to the floor and leave for sufficient time to react with the soiling. Using a 165 rpm rotary machine fitted with a rotary scrubbing brush or, if necessary, a scrubbing pad, machine scrub the floor and then pick up the slurry with a wet vacuum. Rinse thoroughly with clean, warm water, pick up with a wet vacuum and leave to dry thoroughly.
- Other cleaning methods such as a deck scrubber or mop and bucket system can be used with the appropriate neutral or alkaline cleanser - full details are available from Polyflor.

**APPLICATION OF A FLOOR DRESSING**

- A floor dressing or maintainer containing polish should not be applied to Polysafe Wood FX Acoustic, as this may impair the slip resistance but, if in doubt, consult our Technical Support staff.



- Always follow the Health and Safety guidance provided.  
**REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**

- Cleaners and detergents should be diluted as per the manufacturers' instructions. For recommended products, see the Polyflor Approved Maintenance Products sheet located within the Technical section of [www.polyflor.com](http://www.polyflor.com).

Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis.

- For further clarification and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

# APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

## MAINTENANCE PRODUCTS

PRODUCT	DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	BRITISH NOVA Tel: 01295 254030	PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	ECOLAB LTD Tel: 01793 511221 www.ecolab.com	JOHNSON/DIVERSEY Tel: 01604 783500 www.johnsondiversey.co.uk	SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk
NEUTRAL CLEANSER	Active Cleaner	Liquid 99	Prodet	High Class	Brial Action Plus	Taski 300 Carefree Stride 1000	Neutra scrubber dryer detergent
ALKALINE CLEANSER		Novaways Novaways Multi Purpose Sanitiser	Alkleen Ultrapac Renovate Powerclean	E.M.C Versatile Lift	Gloss Express Imi Orange Imi Top Powerclean Imi Action Plus	Brillo Cleaner/Degreaser Carefree Stride 2000 Sprint Hard Surface Cleaner Aggressor	HD Degreaser Triple Selcien Multi Purpose Cleaner
GERMICIDAL CLEANSER		Novacross Non food areas Novacross (unperfumed) Food areas	Protect	Final Touch Esteem Lift	Bioscan	Lifeguard Cleaner/Disinfectant Conc. Shield Lifeguard cleaner Disinfectant Trigger	Selguard Selgeine
MAINTAINER/WASH & WAX	Floor Cleaner R1000	Novacare Novacare Lime-lite	Protreat	Easy Shine Clean & Shine Easy Shine	Formula 71 Indur Brillant Plus Spirit Restorer Indur Top	Carefree Maintainer Carefree Mop & Shine Carefree Stride 3000 Taski Tensol	Selsheen Minit Glass Fast Lane
DRY BRIGHT EMULSION POLISH	Floor Shine	Nova Long Life Nova Long Life Satin Finish	Proshine	Sustain Mexepol Enhance	Isi Star Phazer Isi Star Lodan Star Phazer Lodan Star Tuklar Medical	Carefree Satin Carefree Eturnum Carefree Emulsion	Selbrite Diamond Bright
SEMI BUFFABLE EMULSION POLISH	Floor Mat	Nova Supercote		Ovacryl		Carefree Buffable Floor Polish	Selxel Seldur
FULLY BUFFABLE EMULSION POLISH		Nova Superphalte		Easy Shine	Gemstar Laser Phazer Gem Star Laser		Selgio
POLISH STRIPPER	Clean & Strip	Nova Starbrite Nova 2001	Prostrip	Easystrip Sure Strip	Benduroil Maxx Benduroil Top Strip	Carefree Stripper Carefree Speed Stripper	Selate Selspeed
POWER CLEANER (Spot Cleaner)	Turbo Strip	Cleanol Lift		Lift		Sprint Spitfire	

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at [www.polyflor.com](http://www.polyflor.com)

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM) [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)  
UK SAMPLE REQUESTS: +44 (0)161 767 2551

*James Halstead*  
FLOORING



**POLYFLOR**<sup>TM</sup>  
COVERING THE WORLD