

**POLYFLOR 2000 PUR**

- BRE Global Environmental A+ Rating ENP 336
- Attractive, high-performance, heavy duty floorcovering
- Polyurethane reinforcement for a low cost, lifetime polish-free maintenance regime

**SPECIFICATION**



2.0mm  
2.5mm



2m x 20m = 40m<sup>2</sup>  
2m x 15m = 30m<sup>2</sup>



300 x 300mm  
4.5m<sup>2</sup>  
3.6m<sup>2</sup>



608 x 608mm  
5.17m<sup>2</sup>  
-



3550g/m<sup>2</sup>  
4552g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
EN 649  
ASTM F1913  
ASTM F1700  
Agrément – G5ws



**REACTION TO FIRE**  
EN 13501-1 Class Bfl-S1  
EN ISO 9239-1 ≥8kw/m<sup>2</sup>  
EN ISO 11925-2 Pass  
ASTM E648<sup>†</sup> Class 1

†2.0mm



**SLIP RESISTANCE**  
EN 13893 Class DS  
AS/NZS 4586 R9



**ABRASION RESISTANCE**  
EN 649 Group M



**ELECTRICAL BEHAVIOUR**  
(body voltage)  
EN 1815 ≤2kV  
Classified as 'antistatic'



**MARITIME USAGE**  
American Bureau of Shipping<sup>†</sup>  
US Coast Guard Approved  
Marine Equipment Directive<sup>†</sup>  
96/98/EC as amended 2002/75/EC  
SOLAS 74 †2.0mm



**VOC EMISSIONS**  
AgBB VOC test: Pass  
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)



**ENVIRONMENTALLY PREFERABLE FLOORING**  
BRE Global Environmental A+ Rating ENP 336 in the Green Guide to Specifications. Polyflor 2000 PUR is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at [www.polyflor.com/environment](http://www.polyflor.com/environment)



**AGRÉMENT ASSURANCE**  
Polyflor 2000 PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



**HYGIENE**  
This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



**APPLICATIONS**  
Polyflor 2000 PUR is especially recommended for hospitals, schools, offices, supermarkets and institutional buildings, where an easy to maintain, hardwearing floorcovering with an attractive, modern appearance is required.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM) [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)  
UK SAMPLE REQUESTS: +44 (0)161 767 2551

*James Hulstead*  
FLOORING



POLYFLOR  
**2000 PUR**

**HOMOGENEOUS**

**PERFORMANCE AND PROPERTIES**



Refer to BRE Global ratings on [www.greenbooklive.com](http://www.greenbooklive.com)

