

POLYFLOR 2000 PUR

- BRE Global Environmental A+ Rating ENP 336
- Attractive, high-performance, heavy duty floorcovering
- Polyurethane reinforcement for a low cost, lifetime polish-free maintenance regime

SPECIFICATION

2.0mm	2m x 20m = 40m ²	300 x 300mm	608 x 608mm	3550g/m ²
2.5mm	2m x 15m = 30m ²	4.5m ²	5.17m ²	4552g/m ²
		3.6m ²	-	



GENERAL PERFORMANCE
EN 649
ASTM F1913
ASTM F1700



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E662† <450
ASTM E648† Class 1

†2.0mm



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 660-2 Group M



ELECTRICAL BEHAVIOUR
(body voltage)
EN 1815 <2kV
 Classified as 'antistatic'



MARITIME USAGE
American Bureau of Shipping†
US Coast Guard Approved
Marine Equipment Directive†
96/98/EC
SOLAS 74 †2.0mm



VOC EMISSIONS
AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
GBCA Compliant (Green Tag Approval):† Gold
Finnish M1 Classification:† Pass
Swedish B.P.D (FLEC test):† Best Class

†2.0mm



CASTOR CHAIR
(continuous use)
 Suitable



INDENTATION RESIDUAL
ASTM F970 (Modified)
 Static load 750psi



ENVIRONMENTALLY PREFERABLE FLOORING
 Polyflor 2000 PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 336). 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



AGRÉMENT ASSURANCE
 Polyflor 2000 PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE
 This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



APPLICATIONS
 Polyflor 2000 PUR is especially recommended for hospitals, schools, offices, supermarkets and institutional buildings, where an easy to maintain, hardwearing floorcovering with an attractive, modern appearance is required.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Halstead
 FLOORING



2011



POLYFLOR
2000 PUR
 HOMOGENEOUS



PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com

