

SIMPLAY WOOD PU

- Simplay PU loose lay collection
- Authentic reproductions of wood
- Polyurethane surface treatment
- Ideal for heavy commercial environments

SPECIFICATION



5.0mm



0.7mm



10 @ 178 x 1219mm = 2.17m²



8000g/m²



GENERAL PERFORMANCE
EN 649



REACTION TO FIRE
EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass



SLIP RESISTANCE
Class DS (dry condition)*
DIN 51130 - R10
For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges.



ABRASION RESISTANCE
EN 649 Group T



LIGHT FASTNESS
ISO 105-B02 Method 3 ≥6



INDENTATION - RESIDUAL
EN 433 ≤ 0.1mm



DIMENSIONAL STABILITY
EN 434 ≤ 0.25% max.



CASTOR CHAIR (continuous use)
Suitable



THERMAL CONDUCTIVITY
Suitable for underfloor heating
Max. 27°C



VOC EMISSIONS
ENV 13419 AgBB VOC test: Pass
(Low Result)



ACOUSTIC IMPACT SOUND REDUCTION
EN ISO 140-8 ≥9dB



ENVIRONMENTALLY PREFERABLE FLOORING
Simplay PU is 100% recyclable. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



APPLICATIONS
Simplay PU is ideal for all residential areas and heavy commercial areas where a loose lay product is required, such as offices, retail areas and general commercial interiors.



For information regarding handling and installation, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011




Simplay™

Loose Lay vinyl floor tiles

WOOD P₁

PERFORMANCE AND PROPERTIES



POLYFLOR™
COVERING THE WORLD

July 2011