

## EXPONA WOOD PU

- Expona Design PU collection
- Authentic reproductions of classic and contemporary designed materials
- 56 colours and styles - 26 woods, 15 stones and 15 materials
- Borders, inlays, feature strips and grouting strips available in a variety of formats and different colour combinations

### SPECIFICATION



3.0mm



24 @ 152 x 914mm = 3.34m<sup>2</sup>  
 18 @ 152 x 1219mm = 3.34m<sup>2</sup>  
 15 @ 184 x 1219mm = 3.37m<sup>2</sup>  
 14 @ 203 x 1219mm = 3.46m<sup>2</sup>



0.7mm



5100g/m<sup>2</sup>

LUXURY VINYL  
TILES

expona<sup>®</sup> DESIGN

WOOD <sup>®</sup>

### PERFORMANCE AND PROPERTIES



#### GENERAL PERFORMANCE

EN 649



#### REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m<sup>2</sup>  
 EN ISO 11925-2 Pass



#### SLIP RESISTANCE

Class DS (dry condition)  
 DIN 51130 - R9



#### ABRASION RESISTANCE

EN 649 Group T



#### LIGHT FASTNESS

ISO 105-B02 Method 3 ≥6



#### ELECTRICAL BEHAVIOUR (body voltage)

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



#### INDENTATION - RESIDUAL

EN 433 ≤ 0.1mm



#### DIMENSIONAL STABILITY

EN 434 ≤ 0.25% max.



#### CASTOR CHAIR (continuous use)

Suitable



#### THERMAL CONDUCTIVITY

Suitable for underfloor heating  
 Max. 27°C



#### APPLICATIONS

Expona Design PU is ideal for all residential areas and heavy commercial areas such as hotels, offices, schools, hospitals, airports and department stores.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM  
 UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Haleshead  
FLOORING



POLYFLOR<sup>™</sup>  
COVERING THE WORLD