

POLYFLOR STANDARD XL

- BRE Green Guide to Specifications A+ rating ENP 336
- Hardwearing, homogeneous commercial floorcovering
- Duotone marbleised decoration

SPECIFICATION



1.5mm
2.0mm
2.5mm
3.0mm



2m x 27.5m = 55m²
2m x 20m = 40m²
2m x 15m = 30m²
2m x 13m = 26m²



300 x 300mm

-
4.5m²
3.6m²
2.97m²



608 x 608mm

-
5.17m²
-
-



2360g/m²
3200g/m²
4200g/m²
5010g/m²



GENERAL PERFORMANCE

EN 649

ASTM F1913

ASTM F1700

Agrément -1.5mm: G3ws
2.0, 2.5, 3.0mm: G5ws

1.5mm



2.0mm



2.5mm

3.0mm



REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E662 <450 (1.5, 2.0mm)

ASTM E648 Class 1 (1.5, 2.0mm)



SLIP RESISTANCE

EN 13893 Class DS

AS/NZS 4586 R9



ABRASION RESISTANCE

EN 649 Group M



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 ≤2kV (1.5, 2.0mm)
Classified as 'antistatic'



MARITIME USAGE

†2.0mm
Marine Equipment Directive †
96/98/EC as amended 2002/75/EC
SOLAS 74



ENVIRONMENTALLY PREFERABLE FLOORING

BRE Green Guide to Specifications A+ rating ENP 336. Polyflor Standard XL is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



AGRÉMENT ASSURANCE

Polyflor Standard XL has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is, however, the most important defence against infection.



APPLICATIONS

Polyflor Standard XL is recommended for public, institutional and commercial buildings where long life under heavy traffic is required e.g. hospitals, schools, laboratories, offices etc.



Polyflor homogeneous PUR, heterogeneous PUR and Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels. Some alco-based hand gels contain a high concentration of ethanol and to discuss their compatibility with Standard XL, contact Polyflor Customer Technical Services. For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Hulstead
FLOORING



September 2009



POLYFLOR


STANDARD XL

HOMOGENEOUS

PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com



POLYFLORTM
COVERING THE WORLD