

## STONE FX

- Developed from authentic reproductions of stone and granite flooring
- Collection of 12 designs
- Polyurethane reinforced to aid ongoing maintenance

### SPECIFICATION



2.0mm



0.70mm



2m x 20m = 40m<sup>2</sup>



2700g/m<sup>2</sup>



#### GENERAL PERFORMANCE EN 649



#### REACTION TO FIRE EN 13501-1 Class Bfl-s1



#### SLIP RESISTANCE EN 13893 Class DS (dry condition) AS/NZS 4586 R9



#### RESISTANCE TO CHEMICALS EN 423 (ASTM F 1303-99) Excellent chemical resistance



#### LIGHT FASTNESS ISO 105-B02 (Method3) ≥6



#### ABRASION RESISTANCE EN 649 Group T



#### INDENTATION - RESIDUAL EN 433 <0.10mm



#### DIMENSIONAL STABILITY EN 434 <0.40%



#### FLEXIBILITY EN 435 Method A Pass 20mm Ø



#### CASTOR CHAIR (continuous use) EN 425 Pass Suitable for castor chairs



#### THERMAL CONDUCTIVITY Suitable for underfloor heating (Max 27°C)



#### HYGIENE This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



#### ELECTRICAL BEHAVIOUR (body voltage) EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



#### ENVIRONMENTALLY PREFERABLE FLOORING Polyflor Stone FX PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 415) in major use areas such as education and healthcare. Polyflor Stone FX PUR is 100% recyclable. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at [www.polyflor.com/environment](http://www.polyflor.com/environment)



Polyflor Stone FX is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
 WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Halstead*  
FLOORING




2006



# StoneFX™



## PERFORMANCE AND PROPERTIES



**POLYFLOR™**  
COVERING THE WORLD