

SAARFLOOR DIAMANT

- Heavy contract, synthetic rubber sheet floorcovering
- Multicoloured chip decoration
- Embossed surface finish

SPECIFICATION



2.0mm



1.90m x 15m = 28.5m²



3200g/m²



GENERAL PERFORMANCE

EN 1817



REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass



CIGARETTE RESISTANCE

EN 1399 Method A Rating >4
Method B Rating >3



SLIP RESISTANCE

EN 13893 Class DS



ACOUSTICAL IMPACT SOUND REDUCTION

EN ISO 140-8

Rubber floors make a beneficial contribution to impact sound reduction.



ENVIRONMENTALLY PREFERABLE FLOORING

SaarFloor-Systems Diamant has a generic BRE A+/A rating in the Green Guide to Specification, for contract applications.

A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment.



APPLICATIONS

SaarFloor-Systems Diamant is especially recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required.

Prolonged exposure to oil, grease and fats causes deterioration.

SaarFloor-Systems Diamant is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas.

SaarFloor-Systems Diamant is not recommended for exterior use or swimming pool surrounds.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

At the date of issue the data presented is correct.

However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551


James Halstead
FLOORING
2011



SaarFloor
Systems

DIAMANT

PERFORMANCE AND
PROPERTIES



POLYFLORTM
COVERING THE WORLD