

POLYFLOR PRESTIGE PUR

- BRE Global Environmental A+ Rating ENP 336
- Attractive, high-performance, heavy duty floorcovering
- Polyurethane reinforcement for a low cost, lifetime polish-free maintenance regime

SPECIFICATION



2.0mm



2m x 20m = 40m²



300 x 300mm = 4.5m²
608 x 608mm = 5.17m²



3030g/m²



GENERAL PERFORMANCE

EN 649

ASTM F1913

ASTM F1700

Agreement – G5ws



REACTION TO FIRE

EN 13501-1 Class Bfl-S1

EN ISO 9239-1 ≥8kw/m²

EN ISO 11925-2 Pass

ASTM E662 <450

ASTM E648 Class 1



SLIP RESISTANCE

EN 13893 Class DS

AS/NZS 4586 R9



ABRASION RESISTANCE

EN 649 Group P



ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 ≤2kV

Classified as 'antistatic'



INDENTATION RESIDUAL

ASTM F970 (Modified)

Static load 750psi



VOC EMISSIONS

AgBB VOC test: Pass

Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)



ENVIRONMENTALLY PREFERABLE FLOORING

BRE Global Environmental A+ Rating ENP 336 in the Green Guide to Specifications. Polyflor Prestige PUR is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



AGRÉMENT ASSURANCE

Polyflor Prestige PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



APPLICATIONS

Polyflor Prestige PUR is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Hulstead
FLOORING



January 2010



POLYFLOR


PRESTIGE PUR

HOMOGENEOUS

PERFORMANCE AND
PROPERTIES



Refer to BRE Global ratings
on www.greenbooklive.com



POLYFLORTM
COVERING THE WORLD