

**INITIAL CONSTRUCTION CLEAN**

- Sweep, mop sweep or dry vacuum the floor to remove dust, grit and debris.
- Apply a solution of alkaline cleanser, diluted to the manufacturer's instructions, to the floor and leave for sufficient time to react with the soiling. Using a 165 rpm rotary machine fitted with a rotary scrubbing brush or, if necessary, a scrubbing pad, machine scrub the floor and then pick up the slurry with a wet vacuum. Rinse the floor thoroughly with clean, warm water, pick up with a wet vacuum and leave to dry thoroughly.
- **Note 1:** For small areas, where there is no suitable scrubbing machine available, a deck scrubber should be used in conjunction with a wet vacuum or mop and bucket system.
- **Note 2:** For very heavy soiling, dilution rates above the manufacturer's minimum recommendations may be necessary.
- **Note 3:** For Polysafe Hydro, the scrubbing pad should be replaced with a rotary scrubbing brush or a cylindrical type scrubbing machine.

**ROUTINE MAINTENANCE**

- The frequency of each of the operations is dependent upon the type and intensity of traffic.

STANDARD SURFACE FINISH

- Sweep, mop sweep or dry vacuum the floor to remove dust and loose dirt.
- Spot mop regularly. Stubborn black marks can be removed by using the centre disc of a scrubbing pad and a small amount of undiluted alkaline cleanser. Place the disc under the sole of a shoe and rub - this gives greater pressure. Rinse the area well with clean warm water and leave to dry.
- Apply a solution of neutral or alkaline cleanser, diluted to the manufacturer's instructions, to the floor and leave for sufficient time to react with the soiling. Using a 165 rpm rotary machine fitted with a rotary scrubbing brush or, if necessary, a scrubbing pad, machine scrub the floor and then pick up the slurry with a wet vacuum. Rinse thoroughly with clean, warm water, pick up with a wet vacuum and leave to dry thoroughly.

POLYSAFE HYDRO

- Sweep, mop sweep or dry vacuum the floor to remove dust and loose dirt.
- Spot scrub regularly with a deck scrubber.
- Apply a solution of neutral or alkaline cleanser, diluted to the manufacturer's instructions, to the floor and leave for sufficient time to react with the soiling. Using a 165 rpm rotary machine fitted with a bristle brush, cylindrical machine or deck scrubber, scrub the floor and then pick up the slurry with a wet vacuum. Rinse thoroughly with clean, warm water, pick up with a wet vacuum and leave to dry thoroughly.

**APPLICATION OF A FLOOR DRESSING**

- A floor dressing or maintainer containing polish should not be applied to the Polysafe ranges, as this may impair the slip resistance but, if in doubt, consult our Technical Support staff.



- Always follow the Health and Safety guidance provided.

REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.

- Cleaners and detergents should be diluted as per the manufacturers' instructions. For recommended products, see the Polyflor Approved Maintenance Products sheet located within the Technical section of www.polyflor.com.
Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis.
- For further clarification and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR
POLYSAFE™

SAFETY FLOORING

FLOORCARE FOR
POLYSAFE STANDARD,
STRATA
ULTIMA
AND HYDRO.

APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

MAINTENANCE PRODUCTS

| PRODUCT | DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com | BRITISH NOVA Tel: 01295 254030 | PROCHEM Tel: 0208 974 1515 www.prochem.co.uk | EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk | ECOLAB LTD Tel: 01793 511221 www.ecolab.com | JOHNSON/DIVERSEY Tel: 01604 783500 www.johnsondiversey.co.uk | SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk |
|--------------------------------|--|---|--|--|--|--|--|
| NEUTRAL CLEANSER | Active Cleaner | Liquid 99 | Prodet | High Class | Brial Action Plus | Taski 300 Carefree Stride 1000 | Neutra scrubber dryer detergent |
| ALKALINE CLEANSER | | Novaways Novaways Multi Purpose Sanitiser | Alkleen Ultrapac Renovate Powerclean | E.M.C Versatile Lift | Gloss Express Imi Orange Imi Top Powerclean Imi Action Plus | Brillo Cleaner/Degreaser Carefree Stride 2000 Sprint Hard Surface Cleaner Aggressor | HD Degreaser Triple Selcien Multi Purpose Cleaner |
| GERMICIDAL CLEANSER | | Novacross Non food areas Novacross (unperfumed) Food areas | Protect | Final Touch Esteem Lift | Bioscan | Lifeguard Cleaner/Disinfectant Conc. Shield Lifeguard cleaner Disinfectant Trigger | Selguard Selgeine |
| MAINTAINER/WASH & WAX | Floor Cleaner R1000 | Novacare Novacare Lime-lite | Protreat | Easy Shine Clean & Shine Easy Shine | Formula 71 Indur Brillant Plus Spirit Restorer Indur Top | Carefree Maintainer Carefree Mop & Shine Carefree Stride 3000 Taski Tensol | Selsheen Minit Glass Fast Lane |
| DRY BRIGHT EMULSION POLISH | Floor Shine | Nova Long Life Nova Long Life Satin Finish | Proshine | Sustain Mexepol Enhance | Isi Star Phazer Isi Star Lodan Star Phazer Lodan Star Tuklar Medical | Carefree Satin Carefree Eturnum Carefree Emulsion | Selbrite Diamond Bright |
| SEMI BUFFABLE EMULSION POLISH | Floor Mat | Nova Supercote | | Ovacryl | | Carefree Buffable Floor Polish | Selxel Seldur |
| FULLY BUFFABLE EMULSION POLISH | | Nova Superphalte | | Easy Shine | Gemstar Laser Phazer Gem Star Laser | | Selgio |
| POLISH STRIPPER | Clean & Strip | Nova Starbrite Nova 2001 | Prostrip | Easystrip Sure Strip | Benduroil Maxx Benduroil Top Strip | Carefree Stripper Carefree Speed Stripper | Selate Selspeed |
| POWER CLEANER (Spot Cleaner) | Turbo Strip | Cleanol Lift | | Lift | | Sprint Spitfire | |

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



POLYFLOR™
COVERING THE WORLD