

# POLYTRED ACOUSTIC PU

- Hardwearing vinyl floorcovering with impact sound reduction properties

## SPECIFICATION



3.0mm



2m x 20m = 40m<sup>2</sup>



2850g/m<sup>2</sup>



EN 651: 1996



ASTM E648 Class 1  
EN 13501-1 Class Bfl-S1  
EN ISO 9239-1  $\geq 8\text{kw/m}^2$   
EN ISO 11925-2 Pass



ISO 717/2 82 17dB



Class D (dry condition)



EN 651: 1996 Group M



EN 1815 Polytred Acoustic PU does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor. At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
UK FAX: +44 (0)161 767 1128 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM  
WWW.POLYFLOR.COM

*James Hallett*  
FLOORING

POLYFLOR  
**POLYTRED  
ACOUSTIC**

**SPECIALISED**

PERFORMANCE AND  
PROPERTIES