

Standard XL

Attractive, high performance, heavy duty homogeneous floor covering available in a choice of gauges to suit the application. Featuring a duotone marbleised decoration, Standard XL is available in a palette of practical and versatile shades.

Demonstrating outstanding durability and abrasion resistance, Standard XL is recommended for use in public, institutional and commercial buildings where long life under heavy traffic is required.



	Gauge	EN 428/ISO 24346	1.5mm, 2.0mm, 2.5mm 3.0mm
	Roll Size	EN 426/ISO 24341	1.5mm: 2m x 27.5m = 55m ² 2.0mm: 2m x 20m = 40m ² 2.5mm: 2m x 15m = 30m ² 3.0mm: 2m x 13m = 26m ²
	Tile Size	EN 427/ISO 24342	2.0mm: 300mm x 300mm = 4.5m ² 2.0mm: 608mm x 608mm = 5.17m ²
	Total Weight	EN 430/ISO 23997	1.5mm: 2360g/m ² 2.0mm: 3200g/m ² 2.5mm: 4200g/m ² 3.0mm: 5010g/m ²
	General Performance	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
	Use Area	EN 685/ISO 10874	 1.5mm 2.0mm, 2.5mm, 3.0mm
	Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 <450 Class 1 FSV < 300, SDV < 500 1.5mm, 2.0mm 1.5mm, 2.0mm 2.0mm
	Abrasion Resistance	EN 660-2	Group M
	Binder Content	EN ISO 10581	Type II
	Slip Resistance	EN 13893 DIN 51130	Class DS R9
	Residual Indentation	ASTM F970 (Modified) EN 433/ISO 24343-1	≤0.125mm (750 psi) ≤0.10mm 1.5mm, 2.0mm
	Impact Sound Reduction	EN ISO 10140-3	2dB 2.0mm
	Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
	Resistance to Chemicals	EN 423/ISO 26987	Good resistance
	Light Fastness	ISO 105-B02	≥6
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	Maritime Usage	Marine Equipment Directive 2014/90/EU SOLAS 74	Conforms Conforms 2.0mm 2.0mm
	VOC Emissions	Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish MI Classification	Eurofins certified product Pass Certified Certified 1.5mm, 2.0mm 1.5mm, 2.0mm
	Responsible Sourcing	BES 6001	Excellent

Environmentally Preferable Flooring - Polyflor Standard XL achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus.* Generic EN 15804 Environmental Product Declaration (EPD) available on request. Standard XL is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability. *2.0mm

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Polyflor homogeneous PUR, heterogeneous PUR and Polysafe safety flooring ranges are compatible for use with the most commonly used alcho-based hand gels. Some alcho-based hand gels contain a high concentration of ethanol and to discuss their compatibility with Standard XL, contact Polyflor Customer Technical Services. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.
Decoration and shade may vary slightly from the samples shown.

