
























Palettone PUR

Attractive, high performance, heavy duty homogeneous sheet & tile floor covering with a polyurethane reinforcement for low cost, polish free maintenance.

Featuring a solid colour base with complimentary toned highlights, Palettone PUR is available in a palette of 50 contemporary colours. Demonstrating outstanding durability and abrasion resistance, Palettone PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



	Gauge	EN 428/ISO 24346	2.0mm
	Roll Size	EN 426/ISO 24341	2m x 20m = 40m ²
	Tile Size	EN 427 / ISO 24342	608 x 608mm (12 shades)
	Total Weight	EN 430/ISO 23997	2800g/m ²
	General Performance	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
	Use Area	EN 685/ISO 10874	  
	Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2 AS ISO 9239-1	Class Bfl-S1 <450 Class 1 FSV < 300; SDV < 500 Class B
	Abrasion Resistance	EN 660-2	Group T
	Binder Content	EN ISO 10581	Type I
	Slip Resistance	EN 13893 AS 4586 DIN 51130	Class DS R10 R10
	Indentation Residual	ASTM F970 (Modified) EN 433/ISO 24343-1	< 0.125mm ≤ 0.1mm
	Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	VOC Emissions	Indoor Air Comfort GOLD Floorscore Finnish M1 Classification TVOC after 28 days	Eurofins certified product Certified Certified ≤ 10µg/m ³
<p>Environmentally Preferable Flooring - Polyflor Palettone PUR achieves a BRE Global Environmental A+ Rating (Generic) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor Palettone PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.</p>			
<p>PUR - Polyflor Palettone PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.</p>			
	Biological Resistance	ISO 846 Part C	Good
	Clean Rooms	ISO 14644-1	Class 4
	Ease of Radioactive Decontamination	ISO 8690	Excellent
	<p>Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.</p>		
	<p>Agrément Assurance - Polyflor Palettone PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance the appearance and colour will be retained during this period.</p>		
	<p>Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. Decoration and shade may vary slightly from the samples shown.</p>		

