

The Secura luxury vinyl sheet collection features a selection of 22 wood, stone and abstract designs, to complement a variety of interiors. Attractive yet practical, Secura offers 19dB impact sound reduction and is durable and easy to maintain. Available in 2,3 and 4 metre roll widths, Secura is also looselay meaning no adhesive is required.

Ideally suited for use in residential and light commercial applications.



	<b>Gauge</b>	EN 428/ISO 24346	3.0mm
	<b>Wear Layer</b>	EN 429/ISO 24340	0.35mm
	<b>Roll Size</b>	EN 426/ISO 24341	4m x 25m = 100m <sup>2</sup> 3m x 25m = 75m <sup>2</sup> 2m x 25m = 50m <sup>2</sup>
	<b>Total Weight</b>	EN 430/ISO 23997	1780g/m <sup>2</sup>
	<b>General Performance</b>	EN 653 EN ISO 26986	Conforms Conforms
	<b>Use Area</b>	EN 685/ISO 10874	
	<b>Acoustic Impact Sound Reduction</b>	EN ISO 140-8 EN ISO 10140-3	≥19dB ≥19dB
	<b>Resistance to Chemicals</b>	EN 423 ISO 26987	Excellent chemical resistance
	<b>Reaction to Fire</b>	EN 13501-1	Class Bfl-S1
	<b>Abrasion Resistance</b>	EN 653	Group T
	<b>Slip Resistance*</b>	EN 13893 AS 4586 DIN 51130	Class DS (dry condition) R10 R10
	<b>Indentation Residual</b>	EN 433/ISO 24343-1	<0.2mm
	<b>Dimensional Stability</b>	EN 434/EN ISO 23999	<0.40%
	<b>Flexibility</b>	EN 435/EN ISO 24344	(Method A) / Pass 20mm Ø
	<b>Thermal Resistance</b>	ISO 8302	Suitable for underfloor heating 0.0525m <sup>2</sup> K/W 0.525 Tog
	<b>Electrical behaviour (body voltage)</b>	EN 1815	≤2kV Classified as 'antistatic'
	<b>Light Fastness</b>	ISO 105-B02	(Method 3) ≥6
	<b>Castor Chair (continuous use)</b>	ISO 4918	Pass. Suitable for castor chairs.
	<b>Furniture Leg</b>	EN 424	Pass. Type 2 foot
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD Floorscore	Eurofins certified product Certified Product
	<b>Responsible Sourcing</b>	BES 6001	Very Good

**Environmentally Preferable Flooring** - Polyflor Secura achieves BRE Global A rating (Generic) in the Green Guide to Specification in uses areas such as education and healthcare. It is 100% recyclable. Visit [www.polyflor.com/sustainability](http://www.polyflor.com/sustainability).

**PUR** - Polyflor Secura features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.



**Hygiene** - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

\*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.

The data presented is correct at the time of printing. For latest information, please visit our website [polyflor.com](http://polyflor.com).

Decoration and shade may vary slightly from the samples shown.

