

# CAMARO™

The Camaro range features a variety of different wood and stone textures designed to replicate the original material. These are both decorative and practical offering durability, sound reduction and the ability to install and maintain easily. Common use areas for Camaro include mainly residential or light commercial.




	<b>Gauge</b>	EN ISO 24346 (EN 428)	2.0mm
	<b>Wear Layer</b>	EN ISO 24340 (EN 429)	0.3mm
	<b>Plank Size</b>	EN ISO 24342 (EN 427)	36 @ 304.8 x 304.8mm = 3.34m <sup>2</sup> 18 @ 304.8 x 609.6mm = 3.34m <sup>2</sup> 36 @ 152.4 x 609.6mm = 3.34m <sup>2</sup>
	<b>Total Weight</b>	EN ISO 23997 (EN 430)	3600g/m <sup>2</sup>
	<b>General Performance</b>	EN 649 EN ISO 10582	Conforms Conforms
	<b>Use Area</b>	EN ISO 10874 (EN 685)	
	<b>Reaction to Fire</b>	EN 13501-1	Class Bfl-S1
	<b>Abrasion Resistance</b>	EN 649 EN ISO 10582	Group T Type I
	<b>Slip Resistance</b>	EN 13893 DIN 51130 AS 4586	Class DS (dry condition) R10 R10
		For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.	
	<b>Residual Indentation</b>	EN ISO 24343-1 (EN 433)	<0.1mm
	<b>Dimensional Stability</b>	EN ISO 23999 (EN 434)	≤0.1% max
	<b>Thermal Conductivity</b>	ISO 8302	Suitable for underfloor heating. Max 27°C.
	<b>Light Fastness</b>	ISO 105-B02	(Method 3) ≥6
	<b>Castor Chair (continuous use)</b>	ISO 4918 (EN 425)	Suitable
	<b>Electrical Behaviour (body voltage)</b>	EN 1815	≤2kV Classified as 'antistatic'
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD AgBB VOC test FloorScore	Eurofins certified product Very low emissions Certified product
	<b>Responsible Sourcing</b>	BES 6001 SA 8000	Good Approved factory

**Environmentally Preferable Flooring** - Polyflor Camaro PUR achieves BRE Global A+ rating (ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/sustainability](http://www.polyflor.com/sustainability).

**PUR** - Polyflor Camaro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

The data presented is correct at the time of printing. For latest information, please visit our website [polyflor.com](http://polyflor.com).  
**Decoration and shade may vary slightly from the samples shown.**



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913  
 Sample Requests: +44 (0)161 767 2551 | email: [info@polyflor.com](mailto:info@polyflor.com) | [www.polyflor.com](http://www.polyflor.com)

