












Noppe Stud Tile

SaarFloor-Systems Noppe Stud Tile is suitable for very heavy commercial use in areas of high public circulation such as shopping malls, train stations, airports, department stores, hospitals, educational establishments and other public buildings.

Prolonged exposure to oil, grease and fats causes deterioration. SaarFloor-Systems Noppe Stud Tile is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas. SaarFloor-Systems Noppe Stud Tile is not recommended for exterior use or swimming pool surrounds.



	Gauge	EN 428/ISO 24346	3.0mm 4.0mm
	Tile Size	EN 427/ISO 24342	3.0mm: 20 @ 500mm x 500mm = 5m ² 4.0mm: 16 @ 500mm x 500mm = 4m ²
	Total Weight	EN 430/ISO 23997	3.0mm: 4200g/m ² 4.0mm: 5600g/m ²
	General Performance	EN 12199	Conforms
	Use Area	EN 685/ISO 10874	3.0mm  4.0mm 
	Reaction to Fire	EN 13501-1	Class Cfl-S1
	Cigarette Resistance	EN 1399	Method A Rating >4 Method B Rating >3
	Slip Resistance	EN 13893	Class DS
	Acoustical Impact Sound Reduction	EN ISO 10140-3	Rubber floors make a beneficial contribution to impact sound reduction.
	VOC Emissions	AgBB VOC test	Very low emissions

Environmentally Preferable Flooring - SaarFloor-Systems Noppe Stud Tile achieves a BRE Global Environmental Generic A+/A rating. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/sustainability.

 For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 | email: info@polyflor.com | www.polyflor.com

