

Luxury Vinyl Tile

Designer Outlet

LOOSE LAY

October 2026

LOOSE LAY Gauge: 5.0mm ♦ Wear Layer: 0.7mm



2577 White Vintage Wood
185 x 1505mm



2578 Beige Vintage Wood
185 x 1505mm



2519 Brown Mystique Wood
185 x 1505mm



2585 Cold Cracked Concrete
177.8 x 1219.2mm



2587 Dark Grey Ornamental
600 x 600mm



2589 Blue Textile
177.8 x 1219.2mm



2500 Rich Oak
177.8 x 1219.2mm



2541 Black Concrete
457.2 x 457.2mm



2543 Jerusalem Limestone
457.2 x 457.2mm



2545 Ground Limestone
457.2 x 457.2mm



2546 Porcelain Weave
457.2 x 457.2mm



2540 Limed Concrete
457.2 x 457.2mm

Luxury Vinyl Tile

Designer Outlet

LOOSE LAY

October 2026

CHARACTERISTICS	STANDARD	5.0/0.7mm
Type of floor covering	ISO 10582 (EN 649)	Heterogeneous, PVC
Surface treatment		PUR
Total weight	ISO 23997 (EN 430)	8000 g/m ²
Performance classification	ISO 10874 (EN 685)	23, 34, 42
Gauge	ISO 24346 (EN 428)	5.0mm
Wear layer thickness	ISO 24340 (EN 429)	0.70mm
Dimensional stability	ISO 23999 (EN 434)	≤0.10%*
Residual indentation	ISO 24343-1	<0.10mm*
Light fastness	ISO 105-B02 (Method 3)	≥6
Reaction to fire	EN 13501-1	Class Bfl-S1
Slip resistance**	DIN 51130 EN 13893	R10 Class DS
Static electrical propensity	EN 1815	≤2.0 kV classified as 'antistatic'
Castor chair (continuous use)	ISO 4918 (EN 425)	Suitable
Underfloor heating		Suitable, max. 27°C
VOC emissions	AqBB/ABG	Pass
Plank Size		8 @ 185 x 1505mm = 2.23m ² 10 @ 177.8 x 1219.2mm = 2.17m ²
Tile Size		6 @ 600 x 600mm = 2.16m ² 12 @ 457.2 x 457.2mm = 2.5m ²

* Average test value from current production.

** For clarification regarding slip, consult Polyflor technical services.

