

Voyager Transafe PUR



PRODUCT SPECIFICATION

Key Features

- > Heavy-duty safety flooring for road and certain rail applications.
- > Traditional multi-chip decoration
- > Pendulum test - 36+ (slider 96)
- > Sustainable slip resistance
- > PUR for superior cleaning benefits



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	2430g/m ²
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	14	-	40m ²

Performance Requirements	Standard	Result
General Performance	EN 13845 ASTM F1303	Conforms Type II, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845 AS 4586 Appendix D RRL Pendulum Test DIN 51130 / DIN EN 16165 Ann. B Surface Roughness	ESf R10 ≥36 (wet test - 4S Rubber / Slider 96) R10 Rz ≥20µm
Binder Content	ISO 10581	Type I
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 EN 45545-2 AS ISO 9239-1	Class Bfl-S1 Class 1 Meets Class HL1 & HL2 >8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Flexibility	ISO 24344 (EN435)	(Method A) Pass 20mm ø
Light Fastness	ISO 105-B02 (Method 3)	≥6

Sustainability	Standard	Result
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
FloorScore		Certified

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Excellent
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor Ltd. Head Office


PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.


Voyager Transafe PUR




RANGE SHADES




4805 w/r 5570
NCS S 3500-N LRV 37




4540 w/r 2090
NCS S 3502-B LRV 37




4770 w/r 9120
NCS S 4500-N LRV 30




4020 w/r 9200
NCS S 4500-N LRV 27




4760 w/r 4760
NCS S 6500-N LRV 17




4800 w/r 2010
NCS S 3010-Y60R LRV 41




4140 w/r 4140
NCS S 3010-Y30R LRV 39



4870 w/r 4700
NCS S 4030-B LRV 22



4740 w/r 4910
NCS S 5020-R80B LRV 14




4130 w/r 4130
NCS S 4020-B LRV 25




4040 w/r 9230
NCS S 3060-Y90R LRV 12



4490 w/r 4490
NCS S 7502-B LRV 10



4150 w/r 8640
NCS S 8505-Y20R LRV 6



4815 w/r 8640
NCS S 8502-B LRV 6

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.